

SB-909 SAFETY SURFACE ADHESIVE

Page Number: 1/5
Version Number: 3
Revision Date: 08/16/06

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: SB-909 SAFETY SURFACE ADHESIVE

Company Name: SUREBOND
2801 International Lane
Madison, WI 53704
Phone: (608) 237-7554

SECTION 2 - HAZARDS IDENTIFICATION

Routes of Entry: Entry through inhalation and skin most likely.

Effects of Exposure:

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate irritation, drying of the skin and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory irritation, headache, drowsiness and fatigue. High concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

NFPA Hazard Codes: Health: 1 Fire: 3 Reactivity: 0 PPE: B

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Toluene	108-88-3	25 - 40	Y
Heptane	142-82-5	10 - 15	Y

Notes: Remaining ingredients are not considered OSHA hazardous.

SECTION 4 - FIRST AID MEASURES

Eyes: Flush eyes gently with water lifting eyelids occasionally; get prompt medical attention.
Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.
Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flammability Class: I B

Flash Point: 20.0° F (-6.67° C)
Tag Closed Cup

SB-909 SAFETY SURFACE ADHESIVE

Page Number: 2/5
Version Number: 3
Revision Date: 08/16/06

- Explosive Range (LEL/UEL):** LEL: 1%
UEL: 9%
- Extinguishing Media:** Carbon dioxide, dry chemical, foam.
Use water fog to cool material in vicinity of fire.
- Special Fire-fighting Procedures:** Use self-contained breathing apparatus with full facepiece operated in pressure demand with full protective equipment.
- Unusual Fire and Explosion Hazards:** Any closed container may rupture when exposed to extreme heat. Solvent vapors are heavier than air and travel along the ground. Vapors given off are flammable and may be ignited in air explosively.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Steps to be Taken in Case of Spill:** Eliminate all ignition sources. Ventilate confined areas. (Open windows and doors). Wear appropriate protective clothing. Cover with absorbent. Scoop into sealable safety container.

SECTION 7 - HANDLING AND STORAGE

- Handling and Storage Precautions:**
Keep away from heat, spark and flame.
Keep out of reach of children.
Keep container closed while not in use.
Do not cut or burn receptacles that have contained a solvent based product. Do not reuse this container.
Use only in a well ventilated area.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
Toluene	50.00 PPM	N/Est	150.00 PPM	150.00 PPM	100.00 PPM
Heptane	400.00 PPM	N/Est	500.00 PPM	500.00 PPM	400.00 PPM

- Ventilation:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

Personal Protective Equipment:

- Respiratory Protection:** If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

SB-909 SAFETY SURFACE ADHESIVE

Page Number: 3/5

Version Number: 3

Revision Date: 08/16/06

Protective Clothing: Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

Eye Protection: Chemical goggles or safety glasses should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form: Hazy, colorless caulk
Solubility (in water): Insoluble in water
pH Value, +/- .3: N/A
Boiling Range: 195.0° F - 250.0° F (90.56° C - 121.110° C)
Vapor Pressure (mmHg): 54 @ 68.0° F (20.0° C)
Evaporation Rate: 1.8 times faster than n-Butyl Acetate
Vapor Density: Heavier than air
% Volatile, Weight: Approx. 40.%
% Volatile, Volume: N/A
Specific Gravity: 0.92035
VOC (less H₂O or exempt): 370 Gr/L, 40%

Note: Boil range, evaporation rate, vapor density and pressure for solvent only.

SECTION 10 - STABILITY AND REACTIVITY

Stability: This product is stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Incompatibility: Keep away from strong oxidizing agents.

Conditions to Avoid: Keep away from heat, spark, open flames and any ignition source.

Hazardous Decomposition Products: Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP? N/E | IARC Monographs? N/E | OHSA? NO

Chronic Hazards

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage and cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal. Repeated overexposure to TOLUENE may cause liver damage. Toluene has been found to cause kidney, lung and spleen damage in laboratory animals.

SECTION 12 - ECOLOGICAL INFORMATION

No data available.

SB-909 SAFETY SURFACE ADHESIVE

Page Number: 4/5
Version Number: 3
Revision Date: 08/16/06

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of following local, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION (not all sizes available)

Ground Transport (DOT) - Domestic

Units GREATER than 5 L i.e. 5 gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: CLASS 3
DOT Label Required: Flammable Liquid, UN1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGII
ERG Code: 128

Air Transport (DOT) - Domestic

Units GREATER than 5 L i.e. 5 gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: CLASS 3
DOT Label Required: Flammable Liquid, UN1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGII
ERG Code: 128

Air Transport (IATA) - International

Units GREATER than 5 L i.e. 5 gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: CLASS 3
DOT Label Required: Flammable Liquid, UN1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGII
ERG Code: 3L

Marine - Ocean Transport (IMDG)

Units GREATER than 5 L i.e. 5 gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: CLASS 3 DOT
Label Required: Flammable Liquid, UN1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII for 50 gal use PG II
EMS Code: F-E, S-D

SB-909 SAFETY SURFACE ADHESIVE

Page Number: 5/5
Version Number: 3
Revision Date: 08/16/06

SECTION 15 - REGULATORY INFORMATION

Sara Title III Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
Toluene	108-88-3	25 - 40

PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
Toluene	108-88-3	25 - 40

The following ingredients are registered for TSCA 12B:

Ingredient Name	CAS Number	Percent
n-Hexane	110-54-3	5 - 10

SARA Section 311/312 Hazard Categories Met: Fire Hazard, Immediate (Acute) and Delayed (Chronic) Health Hazards. Chemical ingredients are listed on the TSCA inventory.

SECTION 16 - OTHER INFORMATION

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method or apparatus mentioned. User must make his/her own investigation to determine the suitability of the information or products for his/her particular purpose, for the protection of the environment and the health and safety of the users of this material.

Abbreviations:
N/A = Not Applicable
N/D = Not Determined
N/Est = Not Established